

What is claimed is:

1. A gas detecting element comprising:

a hollow container;

an optical density detection window that is not gas-permeable formed on one
5 side of said container to allow optical density detection;

a gas-permeable window formed on the opposing side of said container; and

a reagent that exhibits coloration by reaction with a gas to be measured housed
in a space between said windows.

10 2. A gas detecting element in accordance with claim 1, wherein:

said optical density detection window is constituted by affixing a transparent,
non-permeable film to a frame that constitutes said container.

3. A gas detecting element in accordance with claim 1, wherein:

15 said optical density detection window is formed at the same time as injection
molding of said container with a transparent, non-permeable material.

4. A gas detecting element in accordance with claim 1, wherein:

a reagent absorbent material impregnated with said reagent is housed in said
20 space.

5. A gas detecting element in accordance with claim 1, wherein:

a light-reflective surface is formed on the side of said gas-permeable window
facing said reagent absorbent material.

6. A gas detecting device comprising:

a gas exposure portion that opens to a sampling flow path; and

an optical density measuring portion provided with a light-emitting means

facing said exposure portion and light receiving means,

5 wherein said exposure portion and said optical density measuring portion are oppositely disposed in a separateable manner, and a gas detecting element is housed so that a gas inflow side of the gas detecting element faces the gas exposure portion and an optical density detection portion of the gas detecting element faces said optical density measuring portion.

10

7. A gas detecting device according to claim 6, wherein said optical density detection portion and said gas detecting element are constituted so as to maintain airtightness.